Date: 04 August 2021

Reviewers: Dr. Matt Becker

Organization/Code: University of Hawaii, 007698208

Project Title: Draft Groundwater Flow and Velocity Evaluation, Red Hill Bulk Fuel Storage Facility,

No.	Page	Section	Comment	Action
1.	5	4.1, Line 17	which measurements are likely to demonstrate preferential flow? Temperature, conductivity?	
2.	5	4.2, Line 27	Give our discussions, I think hydrophysical logging might take the place of borehole dilution. We will get better velocity numbers from the colloidal borescope so it will be more useful, I think, to get relative inflow rates. Velocity can be obtained also from hydrophysical loggins so nothing is lost by making the substution.	
3.	7	5.2, Line 22	If we substitute hydrophysical logging, then we would need a model to interpret. RAS has their own software, and we can request Tsang and Doughty's Bore II code: https://www.osti.gov/biblio/123 2365-bore-ii	
4.	8	5.3, Line 9	I'm not sure what you mean here. If we property scale shouldn't we get the correct local flows?	

Date:09 August 2021Reviewers:Nicole PalazzoloOrganization/Code:EPA Region 9

Project Title: Draft Groundwater Flow and Velocity Evaluation, Red Hill Bulk Fuel Storage Facility,

No.	Page	Section	Comment	Action			
1.	1	1, Line 13	Despite the CSM being an important document, it is not a AOC deliverable. I would suggested making this clear in the last sentence of this paragraph.				
2.	5	4.2, Line 26	Consider providing an explanation for why these specific wells selected?				
3.	6	4.3, Line 19	Consider providing an explanation for why these specific wells selected?				
4.	8	6, Line 11	Consider adding the proposed field implementation schedule and data sharing/reporting schedules here. Also, can you please provide additional details about schedule as proposed during TWG Meeting #42? Is there a way to streamline some of the activities so we can get results quicker?				
Work	Worksheet #1: Project Quality Objectives (PQO)/Systematic Planning 1 Process Statements						
1.	1.5	2, Line 28	[",,,then the Agencies"}: Suggested revision - "The data generated by this study may provide an additional line of evidence for model and CSM validation."				

Date: 05 August 2021 **Reviewers:** Matt Tonkin

Organization/Code: S.S. Papadopulos & Associates, Inc. (EPA SME)

Project Title: Draft Groundwater Flow and Velocity Evaluation, Red Hill Bulk Fuel Storage Facility,

No.	Page	Section	Comment	Action
			•	into, at the level of an SOP/SAP, but below
1 am ju 1.	1 and 3	g on getting the p	urpose/objectives locked down. Based on our discussions	
			over the last 24 months, I	
			believe that the core purpose	
			of the study is to obtain	
			information on the local scale	
			directions and rates of	
			groundwater flow, as inferred	
			from measurements made	
			within individual boreholes	
			using "intra-well" as opposed	
			to "inter-well" techniques.	
			Intra-well studies will be	
			conducted at different vertical	
			placements within the open-	
			screened interval of each tested well to determine	
			whether there is variation in these quantities at each well	
			location. To the extent	
			practical, I understand that	
			intra-well studies will be	
			conducted both with Red Hill	
			Shaft (RHS) pumping, and	
			not pumping, to identify	
			whether there are measurable	
			differences in these quantities	
			between pumping and non-	
			pumping conditions (this is	
			stated in Section 4 at various	
			locations but should be	
			indicated up-front in the	
			purpose/objectives).	
			Once results from the intra-	
			well studies have been	
			obtained, these can then be	
			combined via inter-well	
			comparisons to infer the	
			variability in directions and	
			rates of groundwater flow, and whether any consistent	
			(systematic) patterns of	
			variability – such as trends –	
			are present or whether the	
			inter-well variability appears to	
			be unsystematic and	
			essentially random.	
			Information obtained from the	
			intra-well studies and inter-	
			well comparisons will be used	
			well compansons will be used	L

No.	Page	Section	Comment	Action
			to corroborate or update and refine the local (RHBSF-focused) conceptual site model (CSM). Subsequently, if necessary and appropriate, these data and the updated CSM will be used to update and potentially re-calibrate one or more of the numerical groundwater flow models.	
2.	3	3.2	This is an important statement: "Since in-well testing provides information at a localized scale, it may not be directly comparable on a well-by-well basis to the information presented in the CSM and GWFM reports." We will need to look to Dr. Becker for his guidance on how information from intrawell studies is upscaled or otherwise compared to larger-scale modeling and mapping studies. It would be good to add additional information to this statement regarding the suite of potential, common, methods for accomplishing this.	
3.	4	4	Following from the call on 8/3, I do wonder whether slug testing or a similar method makes sense to undertake. No, its not absolute nor as reliable on a large scale, but it can definitely provide information on relative transmissivities between wells. Since the individual borescope/other tests will be similar in some sense (they don't directly measure velocities in the aquifer materials, but give a sense of direction and relative velocities) I think the slug tests fall into the same category of information – good relative measures comparable between wells, but for absolutes on the scale of RHS/RHBSF we will need to rely on methods like the TFN work already completed. Obtaining these measurements contemporaneously and as	

No.	Page	Section	Comment	Action
			part of the same field program as the in-well borescope etc. testing would be a nice way to provide a tidy package. (*Note: I don't recall if slug testing was previously performed in the wells – I seem to recall it may have been in a subset, but not in all. Note also that pneumatic tests can be used if a sizeable mechanical slug cannot easily be inserted in the well. And finally, Wilson et al (1997) provide a little info on slug testing compared with simple bail-down tests, and their relative values).	
Work	sheet #1:	Project Quality (Objectives (PQO)/Systematic P	lanning 1 Process Statements
			art and outline. There are some u LA) that it would be good to clear	ses of terms (based on my experience up.
1.	1	1.1	- is Worksheet #1 going to be an Addendum to the main Work Plan? Because I am not sure the first sentence in Section 1.1 is entirely accurate, it seems copied from the main Work Plan. This Worksheet should be introduced as the document addressing the specific PQOs/SPPS of the planned Study.	
2.	1	1.2	- the term principal study question (PSQ) is first introduced here and is the terminology I am more familiar with (PSQ and DQOs, versus PQO and SPPS, although I am very familiar with the systematic planning process). I think it would be good to define for purposes of this study the overlap and the differences between PQO and DQO since both terms are used. As I understand it, DQOs can often dig down into specifics of acceptability of data for intended uses, etc., whereas PQOs are often used at a slightly higher level to define what data will be collected, for what purposes, and who will be the recipients	

No.	Page	Section	Comment	Action
			and users of the data. In this sense, as I understand it, PQOs can be less restrictive on the "quality" and end-uses of the data, as long as the data are gathered as planned, and processed, and distributed as intended to the end users. In this sense, PQO may be the best term / approach for this study - but a definition from the navy perspective for this study would be helpful.	
3.	1	1.3	- may consider adding slug testing/pump-down testing to this, as noted above in comments on the main Work Plan. This section is open on the quality of the information and the quality control procedures. I believe this would be the "meat" of the DQOs (as opposed to PQOs, noted above). Quality control protocols are good; and I would emphasize the manufacturer criteria for the equipment used, and that any explicit dos/donts therein are followed, but not define quantitative/%margin/accepta bility criteria or get too quantitative/prescriptive on the DQOs, because of the difficult setting and what is an exploratory study. I have seen %margin acceptability criteria defined before field studies that upended the work. We don't have explicit thresholds in play here such as standards (although there may be PQLs at play, see Section 1.6).	
4.	2	1.4	- recommend adding a simple figure defining the horizontal extents, so that everyone visualizes the area this study is focused on (essentially, an envelop around the traditional wells)	
5.	2	1.5	this is always the rub. What is "consistent" and what is "differ substantially". To get started, we need an earlier section or statement that	

No.	Page	Section	Comment	Action
			defines what the CSM and GWFM reports "present", so we know what we are comparing to and can have an understanding of what "differ" means. For example (and this is just a first cut): • "Although the various GFWMs constructed by the Navy demonstrate some differences in groundwater flow patterns, the CSM and GWFMs collectively depict fairly uniform groundwater flow conditions beneath the RHBSF, with the direction of flow being predominantly makau-to-makai under simulated hydraulic gradients that are on the order of one foot in 500 feet (0.002)."	
6.	3	1.6	– please see comments on Section 1.3. In addition, though this is not a "lab" study, do the manufacturers have published PQLs for their instrumentation, so we have lower-bounds on what is measurable and meaningful. Documenting these can be very important when dealing with Section 1.5 and what is consistent or inconsistent.	
7.	3	1.7	- may consider adding slug testing/pump-down testing to this, as noted above in comments on the main Work Plan	

Date: 04 August 2021

Reviewers: Bob Whittier / Gerry Beckett

Organization/Code: Hawaii Department of Health (DOH) / Aqui-Ver, Inc. (DOH SME)

Project Title: Draft Groundwater Flow and Velocity Evaluation, Red Hill Bulk Fuel Storage Facility,

No.	Page	Section	Comment	Action
1.	1	1, Line 14	As important, the testing is intended to add insight into the hydrogeologic conditions and likely controls of contaminant fate and transport at appropriate scales of interest, as well as uncertainties therein.	
2.	1	1, Line 23	Add, per above, better understanding of CF&T considerations, uncertainties, and the applicability of EPM assumptions	
3.	1	1, Line 23	RBW: The vertical profiles will also indicate if there is vertical stratification. This knowledge cold be useful in targeting sample depths. RHMW05 is a well where this may be an issue	
4.	3	3, Line 9	RBW: I think it would be appropriate to rephrase to "To address uncertainties about the groundwater flow trajectory and velocities; and the utility of using the Red Hill Shaft to contain a spill" As it is written I interpret the statement to mean "the Navy is doing these test because the regulators are forcing us to". That is not the case, the Navy is doing these tests because there are large number of questions and uncertainties that the regulators have pointed out that have not been adequately addressed.	
5.	4	3.2, Line 7	Those key conclusions/interpretations include: (they are not findings, which implies a direct data element): - Relatively rapid g.w. flow - Mauka - makai general direction - Down-dip flow preference - Clinkers are the controling hydraulic zones etc.	

No.	Dago	Section	Comment	Action
	Page		Comment	Action
6.	4	3.3, Line 9	RBW: I would change the Testing Objectives to say "Gain increased understanding of the groundwater flow trajectory and velocity, and the utility of using the Red Hill Shaft to contain a spill."	
7.	5	4.1, Line 10	RBW: I would change "after" to "during". As stated, it appears unclear what the status of the RHS pumps are during the testing.	
8.	5	4.2, Line 28	RBW: I Would add either RHMW09 or RHMW10; chemistry and drawdown response indicate these are potentially in a different flow zone. This suite of test can inform on the hydraulic relationship between RHMW09, RHMW10, and RHMW19; and the rest of the wells at Red Hill.	
9.	6	4.2, Line 18	and inspect for non-ideal or heterogeneous flow responses.	
10.	6	4.3, Line 29	Substitute or add at least one well on the SE side of the ridge.	
11.	7	4.3, Line 2	or dye tracer depending on the equipment, vendor and processing methods to be determined	
12.	7	4.3, Line 4	RBW: Again, change "pumped" to "pumping" to remove any ambiguity about the RHS during the test.	
13.	7	5.2, Line 23	RBW: Collins and Bianchi, 2020, give Python based program for analyzing BH dilution tests.	
14.	7	5.2, Line 28	Sensitivity to the well flow perturbation adjustment factor (alpha) and variance in interpreted results	